

P. Amstutz
5.11.81

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

08/20/81 WKDROMA 00000052 081393 09730029

FC:10 710.00 CH
C:10 144.00 CH

COMMERCIAL - 08/20/81

12-06-00

77

12/05/00

JCS65 U.S. PTO

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)*(Only for new nonprovisional applications under 37 CFR 1.53(b))*Docket No.
1-22795Total Pages in this Submission
13**TO THE ASSISTANT COMMISSIONER FOR PATENTS**Box Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

VEHICLE WHEEL COVER RETENTION SYSTEM AND METHOD FOR PRODUCING SAME

and invented by:

MICHAEL V. MALONEY, THOMAS E. HECK, JAMES A. LUMM, AND JAMES H. KEMMERERIf a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:☒ **Continuation** ☐ **Divisional** ☐ **Continuation-in-part (CIP)** of prior application No.: 09/473,237

Which is a:

☒ **Continuation** ☐ **Divisional** ☐ **Continuation-in-part (CIP)** of prior application No.: 08/886,264

Which is a:

☒ **Continuation** ☐ **Divisional** ☐ **Continuation-in-part (CIP)** of prior application No.: 08/389,867

X Continuation-in-part (CIP) of prior app. No.: 08/203,058

Enclosed are:

Application Elements☒ Filing fee as calculated and transmitted as described below☒ Specification having 8 pages and including the following:

- a. ☒ Descriptive Title of the Invention
- b. ☐ Cross References to Related Applications (if applicable)
- c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
- d. ☐ Reference to Microfiche Appendix (if applicable)
- e. ☒ Background of the Invention
- f. ☒ Brief Summary of the Invention
- g. ☒ Brief Description of the Drawings (if drawings filed)
- h. ☒ Detailed Description
- i. ☒ Claim(s) as Classified Below
- j. ☒ Abstract of the Disclosure

JCS65 U.S. PTO

09/730029

00/50/12/05/00

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
1-22795

Total Pages in this Submission
13

Application Elements (Continued)

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☒ Formal Number of Sheets 5
- b. ☐ Informal Number of Sheets _____
4. ☒ Oath or Declaration
- a. ☐ Newly executed *(original or copy)* ☐ Unexecuted
- b. ☒ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
- ☒ Incorporation By Reference *(usable if Box 4b is checked)*
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under
Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.
- ☐ Computer Program in Microfiche *(Appendix)*
- ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☐ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☐ Information Disclosure Statement/PTO-1449 ☐ Copies of IDS Citations
12. ☒ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing
- ☐ First Class ☒ Express Mail *(Specify Label No.):* EL621741344US

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
1-22795

Total Pages in this Submission
13

Accompanying Application Parts (Continued)

15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*
16. ☐ Additional Enclosures *(please identify below):*

Request That Application Not Be Published Pursuant To 35 U.S.C. 122(b)(2)

- ☐ Pursuant to 35 U.S.C. 122(b)(2), Applicant hereby requests that this patent application not be published pursuant to 35 U.S.C. 122(b)(1). Applicant hereby certifies that the invention disclosed in this application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication of applications 18 months after filing of the application.

Warning

An applicant who makes a request not to publish, but who subsequently files in a foreign country or under a multilateral international agreement specified in 35 U.S.C. 122(b)(2)(B)(i), must notify the Director of such filing not later than 45 days after the date of the filing of such foreign or international application. A failure of the applicant to provide such notice within the prescribed period shall result in the application being regarded as abandoned, unless it is shown to the satisfaction of the Director that the delay in submitting the notice was unintentional.

17 493730838-150500

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
1-22795


Total Pages in this Submission
13

Fee Calculation and Transmittal

CLAIMS AS FILED

| For | #Filed | #Allowed | #Extra | Rate | Fee |
|--|--------|----------|--------|-----------|----------|
| Total Claims | 28 | - 20 = | 8 | x \$18.00 | \$144.00 |
| Indep. Claims | 3 | - 3 = | 0 | x \$80.00 | \$0.00 |
| Multiple Dependent Claims (check if applicable) <input type="checkbox"/> | | | | | \$0.00 |
| BASIC FEE | | | | | \$710.00 |
| OTHER FEE (specify purpose) | | | | | \$0.00 |
| TOTAL FILING FEE | | | | | \$854.00 |

- ☐ A check in the amount of _____ to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 08-1393 as described below. A duplicate copy of this sheet is enclosed.
- ☒ Charge the amount of \$854.00 as filing fee.
 - ☒ Credit any overpayment.
 - ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
 - ☒ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).


Signature

Dated: December 5, 2000

Douglas V. Pavelko Reg. No. 36,888
MacMillan, Sobanski & Todd, LLC
One Maritime Plaza, Fourth Floor
720 Water Street
Toledo, Ohio 43604
(419) 255-5900

CC:

CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10)Applicant(s): **Michael V. Maloney et al.**

Docket No.

1-22795

Serial No.

Unknown


Filing Date

Herewith

Examiner

Unknown

Group Art Unit

UnknownInvention: **VEHICLE WHEEL COVER RETENTION SYSTEM AND METHOD FOR PRODUCING SAME**I hereby certify that this **patent application and associated documents**

(Identify type of correspondence)

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under

37 CFR 1.10 in an envelope addressed to: The Assistant Commissioner for Patents, Washington, D.C. 20231 on

December 5, 2000

(Date)

Tracy Partin

(Typed or Printed Name of Person Mailing Correspondence)

A handwritten signature in cursive script that reads "Tracy Partin".

(Signature of Person Mailing Correspondence)

EL621741344US

("Express Mail" Mailing Label Number)

Note: Each paper must have its own certificate of mailing.

ABSTRACT OF THE DISCLOSURE

09/730029

A vehicle wheel cover retention system wherein the outboard tire bead seat retaining flange of the associated wheel includes a unique construction for securing a wheel cover to the wheel. In particular, the vehicle wheel includes a disc which defines an outboard facing wheel surface and includes an outboard tire bead seat retaining flange. The outboard tire bead seat retaining flange includes an outer surface having a circumferential, radially inwardly facing groove formed therein. A relatively thin wheel cover (which may or may not conform to the exact contour of the disc) covers at least a portion of the outboard facing wheel disc surface. In particular, the wheel cover includes an outer annular lip which extends into the groove.

TITLE

VEHICLE WHEEL COVER RETENTION SYSTEM

BACKGROUND OF THE INVENTION

5 This invention relates to vehicle wheels and, in particular, to an improved vehicle wheel cover retention system.

Full or partial vehicle wheel covers of the removable type are well known, and have been used for many years to enhance the styling of conventional, stamped wheel discs. Also, it is known to permanently secure a
10 full or partial wheel cover to a vehicle wheel using an adhesive material.

One example of a vehicle wheel construction wherein an ornamental plastic wheel cover having a chrome-plated outer surface is permanently secured to an outboard facing surface of a wheel is disclosed in U.S. Patent No.
15 3,669,501 to Derleth. In the Derleth patent, the wheel cover includes an outer peripheral flange which overhangs the outboard tire bead seat retaining flange of the wheel, an inner peripheral flange which seats against an outboard surface of a hub sleeve, and an intermediate portion which is spaced outwardly from the face of the wheel. An expanding adhesive material is applied to the outboard
20 surfaces of the wheel. When the adhesive material is expanded, it is operative to fill the void between the wheel and the wheel cover to permanently secure the wheel cover to the outboard face of the wheel.

Another example of a vehicle wheel construction having an ornamental wheel cover permanently secured to an outboard facing surface of the wheel is
25 disclosed in U.S. Patent No. 5,031,966 to Oakey. In the Oakey patent, a cast aluminum wheel cover is secured to a disc of a steel wheel using a high density structural adhesive.

*This application is a continuation of 09/473,237 12-27-99
which is a continuation of 08/886,264 7-1-97 Pat 6,007,158
which is a continuation of 08/389,867 2-23-95 Pat 5,664,845
which is a continuation-in-part of 08/203,058 2-28-94 Pat. # 5,435,63*

SUMMARY OF THE INVENTION

This invention relates to a vehicle wheel cover retention system wherein the outboard tire bead seat retaining flange of the associated wheel includes a unique construction for securing a wheel cover to the wheel.

5 In particular, the vehicle wheel includes a disc which defines an outboard facing wheel surface and includes an outboard tire bead seat retaining flange. The outboard tire bead seat retaining flange includes an outer surface having a circumferential, radially inwardly facing groove formed therein. A relatively thin wheel cover (which may or may not conform to the exact contour of the

10 disc) covers at least a portion of the outboard facing wheel disc surface. In particular, the wheel cover includes an outer annular lip which extends into the groove. The groove functions, in part, to hide a peripheral edge of the cover. Preferably, an adhesive material is applied to the outboard facing wheel surface of the disc, and the cover is then pressed against the adhesive covered to

15 permanently secure the wheel cover to the disc. Such a construction is especially advantageous when it is desired to produce a "chrome plated" wheel. It has been found that the cost of forming the cover, chrome plating the cover, and then securing it to the disc is substantially less than plating a wheel disc by a conventional process.

20 Other advantages of this invention will become apparent to those skilled in the art from the following detailed description of the preferred embodiment, when read in light of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

25 FIG. 1 is an exploded perspective view of an improved vehicle wheel constructed in accordance with the present invention

FIG. 2 is a plan view showing the adhesive pattern for the vehicle wheel illustrated in FIG. 1.

FIG. 3 is a cross-sectional view of a selected portion of the vehicle wheel illustrated in FIG. 1.

FIG. 4 is an enlarged cross-sectional view of a selected portion of the vehicle wheel illustrated in FIG. 3

5 FIG. 5 is a cross-sectional view similar to FIG. 3, and showing an alternate embodiment of a vehicle wheel construction.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, there is illustrated in FIG. 1 an exploded perspective view of an improved vehicle wheel, indicated generally at 10, and constructed in accordance with the present invention. The vehicle wheel 10 shown in this embodiment is a full face fabricated type of wheel, and includes a rim 12, a full face wheel disc 14, a wheel cover 16, and a cap 18. However, it will be appreciated that the invention is applicable for use with other wheel constructions. For example, the wheel can be a "bead seat attached wheel" (such as shown in FIG. 4 of U.S. Patent No. 5,188,429 to Heck et al.), a "well attached wheel" (such as shown in FIG. 3 of U.S. Patent No. 5,188,429 to Heck et al.), a one-piece cast or forged alloy wheel (such as shown in U.S. Patent No. 5,078,453 to Siwek), or a wheel construction including a partial rim and a full face wheel disc (such as shown in U.S. Patent No. 5,027,508 to Cissell II), all of these patents incorporated herein by reference.

The rim 12 is preferably painted black, and is a fabricated rim constructed of steel, aluminum, or other alloy materials. The rim 12 includes an inboard tire bead seat retaining flange 20, an inboard tire bead seat 22, a generally axially extending well 24, and an outboard tire bead seat 26.

The disc 14 is a forged, cast or fabricated disc constructed of steel, aluminum, or other alloy materials, and includes a generally centrally located wheel mounting surface 30, and an outer annular flange 32. The wheel

mounting surface 30 is provided with a centrally located pilot aperture 34, and a plurality of lug bolt receiving holes 36. The lug bolt receiving holes 36 receive lug bolts and nuts (not shown) for securing the wheel 10 on an axle (not shown) of a vehicle. The outer annular flange 32 of the disc 14 defines an outboard tire bead seat retaining flange of the wheel 10, and includes an outer surface 40 and an inner surface 42. The disc 14 further includes a plurality of decorative openings or windows 38. Preferably, the annular flange 32 is painted silver and the rest of the disc 14 is painted black.

As shown in this embodiment, the cap 18 is secured to the disc 14 by a plurality of fasteners 19 (only one fastener 19 being illustrated). The fasteners 19 extend through openings 21 formed in the cap, and are received in threaded openings 23 provided in the wheel mounting surface 30 of the disc 14.

As best shown in FIG. 4, the annular flange 32 of the disc 14 defines a radially extending outer end surface 50, an axially extending inner side surface 52, and an axially extending outer side surface 54. To assemble the wheel 10, an outboard end 28 of the rim 12 is positioned against the inner surface 42 of the disc 14 and a weld 44 is provided to join the disc 14 and rim 12 together as shown in FIG. 3.

In accordance with the present invention, the outer surface 40 of the disc 14 is provided with a circumferential, radially inwardly facing groove or recess 46. Preferably, the groove 46 is formed by a machining operation to predetermined specifications. However, the groove 46 can be formed by other methods. For example, the groove 46 can be formed by a stamping operation or a spinning operation.

As best shown in FIG. 4, the groove 46 is defined by a first surface 58 which extends in a generally axial direction, and a second surface 56 which extends in a generally radial direction a predetermined distance X. In particular, the surfaces, 58, and 56 are oriented at predetermined angles A and B,

respectively, relative to a reference line C which is generally parallel to the wheel axis. The angle A is in the range of 0° to 30° , and the angle B is in the range of 60° to 120° . Preferably, the angle A is approximately 20° , and the angle B is approximately 90° . As will be discussed below, the distance X is
 5 selected so that an outer annular lip of the wheel cover 16 is completely recessed within the groove 46.

The wheel cover 16 shown in this embodiment is preferably formed from stainless steel having a thickness of approximately 0.020 inch, and is painted or chrome plated. The wheel cover 16 is prefabricated to generally match the
 10 particular configuration of the outboard facing surface of the disc 14. In particular, the wheel cover 16 includes a plurality of openings 60 which correspond to the windows 38 formed in the disc 14, and an enlarged central opening 62.

The openings 60 in the cover 16 are preferably formed by a stamping
 15 operation. As best shown in FIG. 3, edges 63 of the openings 60 extend slightly past edges 39 of the windows 38. As a result of this, when the cover 16 is secured to the disc 14, the completely assembled wheel 10 of the present invention has the appearance of a "chrome plated" wheel.

The cover 16 further defines an outer surface 64, an inner surface 65, and
 20 an outer annular lip 65. The annular lip 66 of the cover 16 defines an outer peripheral edge 68 which is preferably slightly spaced from the adjacent second surface 56 of the groove 46 to form a gap 72 therebetween to accommodate small dimensional changes in the outer edge 68 of the wheel cover 16; however, in some instances, there may be some contact between the outer edge 68 of the
 25 cover 16 and the second surface 56 of the groove 46. Also, the outer annular lip 66 of the cover 16 is prefabricated in such a manner (as shown in phantom in FIG. 4) that, when the cover 16 is positioned on the disc 14, inner surface 66A of

the lip 66 is biased outwardly against surface 58 of the groove 46. The outer peripheral edge 68 of the cover 16 defines an inner circle 68A.

In order to permanently secure the cover 16 to the disc 14, an adhesive 70, such as a two-part epoxy, is utilized. A suitable epoxy is FUSOR 380/382
5 manufactured by Lord Corporation. As shown in FIG. 2, the adhesive 70 is preferably applied on the outboard face of the disc 14 in a predetermined pattern as represented by the heavy lines consisting of an inner circle 70B, an outer circle 70A, and angled radial lines 70C.

The pattern of the adhesive 70 is selected so that when the wheel cover 16
10 is positioned on the disc 14 and pressure applied thereto, a smearing of the adhesive 70 over substantially the entire outboard face of the disc 14 occurs. The adhesive 70 functions to permanently secure the cover 16 to the disc 14. Also, since the adhesive 70 covers substantially the entire interface between the cover 16 and the disc 14, it is effective to provide a seal and prevent water, mud,
15 and other debris from entering between the cover 16 and the outboard facing surface of the disc 14.

The distance X of the second surface 56 of the groove 46 is at least equal to the combined thicknesses of the wheel cover 16 and the adhesive material so that the inner circle 68A of the wheel cover 16 is recessed relative to the inner
20 side surface 52 of the annular flange 32 of the disc 14. This effectively hides the outer peripheral edge 68 of the cover 16. This is also important to ensure that the wheel cover 16 does not interfere with the attachment of a wheel balance weight 90 (as shown in FIG. 5)

FIG. 5 illustrates an alternate embodiment of a wheel cover 80 which is
25 similar to the wheel cover 16 shown in FIGS. 1 and 3, except that the wheel cover 80 has a styled configuration different from the associated wheel disc. This enhances the styling of the associated vehicle wheel as compared to the disc. It also enables different styled covers to be used with a common disc.

In particular, the wheel cover 80 includes a predetermined profile which positions an inner surface 82 thereof a substantial distance from the outboard facing surface of the disc 14. In this embodiment, an expandable foam adhesive material 84 is used to permanently secure the cover 80 to the disc 14.

- 5 Preferably, the adhesive material 84 is applied to the outer surface of the disc 14 in a predetermined pattern so that when the adhesive material 84 expands, it covers substantially the entire interface between the cover 80 and the disc 14. The adhesive material 84 functions to permanently secure the cover 80 to the disc 14, and prevents water, mud, and other debris from entering therebetween.

- 10 Also, the cover 80 includes an outer annular lip 86 which is prefabricated and secured in a manner similar to that discussed above with respect to the cover 14 of FIGS. 1-4.

- It will be appreciated that while the invention has been illustrated and described as having the wheel cover cover only a portion of the outboard facing surface of the disc, other wheel cover configurations are possible. For example, a wheel cover (not shown) can be provided to cover substantially the entire outboard facing surface of the disc.

- In accordance with the provisions of the patent statutes, the principle and mode of operation of this invention have been described and illustrated in its preferred embodiment. However, it must be understood that the invention may be practiced otherwise than as specifically explained and illustrated without departing from the spirit or scope of the attached claims.